


Product Data Sheet

MASONRY PAVER

Steel Grey Ashlar Classic 60mm



| Product Information | |
|---------------------------------------|-------------------|
| Work Size (mm) | 1000 x 1100 layer |
| Dimensional Category | DPA2 |
| CMAA Shape Category | Type C |
| Approximate Unit Weight (kg) | - |
| Approximate No. per m ² | 11 |
| No. Per Pack | 10 layers |
| Nominal Pack Weight (kg) ³ | 1550 |
| Breaking Load (kN) ¹ | >5 |
| Mean Abrasion Index (Va) ² | <12 |
| Slip Resistance Category | P5 |
| Cold Water Absorption (%) | <5 |
| Coefficient of Contraction (mm/m) | <0.8 |
| Durability Class | General Purpose |
| Potential to Effloresce | Slight |
| Liability to Lime Pitting | Nil |
| Solar Absorption Rating | Medium to Dark |

This technical information represents average properties obtained from production runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 4586 are used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic conditions. Colours are indicative only. Information subject to change without notice.

¹ At 28 days

² At 90 days

³ Includes +3% for moisture

Ashlar Classic 60mm Masonry Paver Range



Charcoal



Limestone



Golden Sand



Steel Grey