


# Product Data Sheet

CLAY FACE BRICK

## Grey Coda Range




Product Information	Cored
Work Size (mm)	230 x 110 x 76
Dimensional Category	DW1
Approximate Unit Weight (kg)	2.8
Approximate No. per m <sup>2</sup>	48.5
No. Per Pack	264
Pack Weight (kg) <sup>1</sup>	761
Characteristic Unconfined Compressive Strength (MPa) f <sub>uc</sub>	>12
Cold Water Absorption (%)	<12
Coefficient of Expansion (mm/m)	<0.8
Durability Class	Exposure Grade - Marine
Initial Rate of Absorption (kg/m <sup>2</sup> /min)	<1.4
Potential to Effloresce	Nil to Slight
Liability to Lime Pitting	Nil to Slight
Core Percentage	<30
Solar Absorption Rating	Medium to Dark
Fire Resistance - Insulation (minutes)	90

This technical information represents average properties obtained from production runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 4586 are used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic condition. Colours are indicative only. Information subject to change without notice.

<sup>1</sup> Includes +3% moisture

### Coda Clay Face Bricks



Red



Grey

Note: If you require specific or improved product specifications please contact your Sales Representative.