



CLAY FACE BRICK

Classic Range



STANDARD GREY

PRODUCT INFORMATION	CORED	SOLID
Work Size (mm)	230 x 110 x 76	230 x 110 x 76
Dimensional Category	DW1	DW1
Approximate Unit Weight (kg)	2.6	3.7
Approximate Bricks Per m ²	48.5	48.5
Bricks Per Pack	264	264
Pack Weight (kg) <i>includes+3% moisture</i>	707	1006
Unconfined Compressive Strength (MPa)	>15	>18
Cold Water Absorption (%)	<12	<12
Durability Class	General Purpose	General Purpose
Potential to Effloresce	Nil-Slight	Nil-Slight
Susceptibility to Lime Pitting	Nil	Nil
Core/Void Percentage	<30	-
Fire Resistance - Insulation. Unrendered (minutes)	90	90
Colours	Laneway Vibe Nouveau Grey	Laneway Vibe Tumbled

This technical information represents average properties obtained from production runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 3700 is used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic conditions. Information subject to change without notice.

If you require specific or improved product specification, please contact your Sales Representative.



For more information
about Midland Brick



Call us on **13 15 40**



Visit our website at **midlandbrick.com.au**



Drop into a Midland Brick Selection Centre or Reseller



DISCLAIMER. The information presented herein is supplied in good faith and to the best of our knowledge was correct at the time of preparation. No responsibility can be accepted by Midland Brick, its staff or its agents for any errors or omissions. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by Midland Brick, its staff or its agents for any loss or damage caused by any person acting or refraining from action as a result of this information.