

## Bremer Bay



Product Information	BREMER BAY	BREMER BAY 190 SNAP	1CSE SOLID BREMER BAY SOLID	1CSE CORED BREMER BAY
<b>Size</b>	290x90x162	290x90x162		
<b>Dimensional Category</b>	DW1	DW1		
<b># Pack</b>	132	132		
<b>Approximate Unit Weight (kg)</b>	5.4	5.4		
<b>Approx Pack Weight</b>	734	734		
<b>Approximate Bricks Per m2</b>	19.4	19.4		
<b>Mean Unconfined Compressive Strength (MPa)</b>	>10	>10		
<b>CWA</b>	<13	<13		
<b>Core/Void Percentage</b>	<35	<35		
<b>Durability Class</b>	General Purpose	General Purpose		
<b>Potential to Effloresce</b>	Nil-Slight	Nil-Slight		
<b>Liability to Lime Pitting</b>	Nil	Nil		
<b>FRL (min) Single Leaf unrendered</b>	60	60		

This technical information represents average properties obtained from production runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 3700 is used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic conditions. Information subject to change without notice. If you require specific or improved product specification, please contact your Sales Representative.



For more information about Midland Brick

**A: 260 Kalamunda Road, South Guildford, WA 6055**  
**P: 6313 1000**

DISCLAIMER. The information presented herein is supplied in good faith and to the best of our knowledge was correct at the time of preparation. No responsibility can be accepted by Midland Brick, its staff or its agents for any errors or omissions. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by Midland Brick, its staff or its agents for any loss or damage caused by any person acting or refraining from action as a result of this information.