


# Nouveau Grey Tumbled



PRODUCT INFORMATION	STD CORED NOUVEAU GREY RUMBLED	STD SOLID NOUVEAU GREY RUMBLED
Size	230x110x76	230x110x76
Dimensional Category	DW1	DW1
# Pack	264	264
Approximate Unit Weight (kg)	2.6	3.7
Approx Pack Weight	707	1006
Approximate Bricks Per m <sup>2</sup>	48.5	48.5
Unconfined Compressive Strength (MPa)	>15	>18
CWA	<12	<12
Core/Void Percentage	<30	-
Durability Class	General Purpose	General Purpose
Potential to Effloresce	Nil-Slight	Nil-Slight
Liability to Lime Pitting	Nil	Nil
FRL (min) Single leaf unrendered	90	90

This technical information represents average properties obtained from productions runs. If specific results are required, samples should be taken from current production runs. AS/NZS 4456 and 3700 is used as applicable. Durability classifications are based on product knowledge under local (Perth) climatic conditions. Information subject to change without notice. If you require specific or improved product specification, please contact your Sales Representative.



For more information about Midland Brick

**A: 260 Kalamunda Road, South Guildford, WA 6055**  
**P: 6313 1000**

DISCLAIMER. The information presented herein is supplied in good faith and to the best of our knowledge was correct at the time of preparation. No responsibility can be accepted by Midland Brick, its staff or its agents for any errors or omissions. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by Midland Brick, its staff or its agents for any loss or damage caused by any person acting or refraining from action as a result of this information.